


Personal Protective Equipment and Safe Work Apparel



Preparer:




 Jill S. Logsdon
 UPF Construction Issues Management

09/21/21

 Date


Approval:



 Kieran S. Kelly
 UPF ES&H Manager, BNI

09/21/21


 Date



 Jamie M. Horning
 UPF ES&H Manager, CNS

09/21/21

 Date



 Robert S. Solberg
 UPF Site Manager

09/21/21

 Date

10/21/21

 Effective Date

REVISION LOG

Revision 13	<input checked="" type="checkbox"/> Intent <input type="checkbox"/> Non-Intent
<ul style="list-style-type: none"> • Revised Section 3.0, <i>Requirements</i>, in response to Condition Report 25774-000-GCA-GAM-03184, <i>Arc Between Welder Safety Toe Boot/Welding Whip (ORPS Reportable NA-UPO-CNS-UPRPROJ-2021-0007)</i> <ul style="list-style-type: none"> ◦ Added Section 3.1.11, <i>Body Protection</i>, and Section, 3.1.11.1 <i>Welding and Associated Hot Work Activities</i>, to specify PPE requirements for personnel performing welding and hot work as requested by the Authority Having Jurisdiction • An evaluation determination has been performed confirming that this Procedure does not implement requirements tracked in the Programmatic Requirements Management System (PRMS) • No forms have been revised as a part of this revision • Other changes include: <ul style="list-style-type: none"> ◦ Revised Section 3.1.1, <i>Safe Work Apparel</i>, to clarify appropriate clothing/apparel at UPF sites including a NOTE regarding the use of arm sleeves ◦ Revised Section 3.1.3, <i>Head Protection</i>, to clarify use and upkeep of head protection ◦ Revised Section 3.1.4, <i>Eye and Face Protection</i>, to include use and maintenance requirements ◦ Revised Section 3.1.6, <i>Hand Protection (Gloves)</i>, to require the use of hand protection in all active Construction and Warehousing areas and to include new minimum requirements for the selection of hand protection ◦ Added new Sections 3.1.3.1, <i>Alternate Forms of Head Protection</i>; 3.1.4.1, <i>Goggles and Sealed Eyewear</i>; 3.1.4.2, <i>Face Shields</i>; and 3.1.4.3, <i>Welding Helmets (Hoods)</i> ◦ Added Appendix B, <i>Guide for Shade Numbers in Welding</i> ◦ Updated references ◦ Updated acronyms and definitions ◦ Editorial changes • This revision is a total rewrite; because of the extent of changes, revision bars are not shown 	
Revision 12	<input checked="" type="checkbox"/> Intent <input type="checkbox"/> Non-Intent
<ul style="list-style-type: none"> • This revision incorporates the changes identified in and supersedes PRCN-UPF-CP-205-R11-01, Rev. 0, and PRCN-UPF-CP-205-R11-02, Rev 0. • No forms have been edited as part of this revision. • A periodic review has been completed for this revision and addresses issues identified in DPR-UPF-CP-205-11. • An evaluation determination has been performed confirming that this Command Media implements no quality requirements as tracked in the Programmatic Requirements Management System (PRMS). • Description of other changes incorporated; examples are listed below: <ul style="list-style-type: none"> ◦ Revised Section 3.1.1, <i>Safe Work Apparel—Construction/Warehousing Areas</i>, to clarify minimum clothing requirements. ◦ Revised Section 3.1.12, <i>High-Visibility Apparel</i>, to remove Equipment Spotter. ◦ Deleted Section 3.1.4, <i>Safe Work Apparel—Office Facilities</i>. ◦ Added reference to E-POL-0050, <i>Standards of Conduct and Appearance</i>, for office work. ◦ Changed phrasing in Section 3.1.3, <i>Head Protection</i>. ◦ Changed phrasing in Section 3.1.4, <i>Eye and Face Protection</i>. ◦ Moved bullets in Section 3.1.6 to 3.1.6.1, <i>Selection of Hand Protection</i>, and updated note. 	

Personal Protective Equipment and Safe Work Apparel

- Changed phrase Construction Support Areas to Construction/Warehousing Support Facilities throughout and added to Definitions.
- Updated Acronyms and template.

Previous revisions on record

CONTENTS

1.0 INTRODUCTION.....	5
1.1 Purpose.....	5
1.2 Scope.....	5
2.0 RESPONSIBILITIES.....	5
2.1 Site Manager.....	5
2.2 Environmental, Safety and Health Manager, BNI	5
2.3 Environmental, Safety and Health Representative, BNI	5
2.4 Responsible Superintendent.....	5
2.5 Supervisor.....	6
2.6 PPE User/Worker.....	6
3.0 REQUIREMENTS	6
3.1 Criteria for PPE and Safe Work Apparel.....	7
3.1.1 Safe Work Apparel—Construction/Warehousing Areas.....	7
3.1.2 Footwear—Construction/Warehousing Areas.....	7
3.1.3 Head Protection	8
3.1.4 Eye and Face Protection.....	9
3.1.5 Hearing Protection	10
3.1.6 Hand Protection (Gloves).....	10
3.1.7 Respiratory Protection Equipment	11
3.1.8 Fall Protection Equipment.....	11
3.1.9 Electrical Protection Equipment	11
3.1.10 High-Visibility Apparel	11
3.1.11 Body Protection.....	12
4.0 RECORDS	13
5.0 REFERENCES.....	13
5.1 Source References	13
5.2 Interfacing References	13
6.0 SUPPLEMENTAL INFORMATION	14
APPENDIX A Acronyms and Definitions	15
APPENDIX B Guide for Shade Numbers in Welding.....	16

1.0 INTRODUCTION

1.1 Purpose

This Procedure describes how personal protective equipment (PPE) is selected, inspected, and maintained at the Uranium Processing Facility (UPF).

1.2 Scope

This Procedure is applicable to UPF construction site personnel, subcontractors, vendors, and visitors throughout the duration of the Project.

This Procedure does not address attire worn in project office facilities (e.g., 1060 and 1099 Commerce Park). Reference E-POL-0050, *Standards of Conduct and Appearance*, for further guidance.

2.0 RESPONSIBILITIES

2.1 Site Manager

The Site Manager has the overall responsibility for implementing this Procedure. The Site Manager is also responsible for:

- Ensuring that all project personnel actively participate in the PPE program
- Providing worker support, facilities, and other resources necessary to effectively carry out the PPE program

2.2 Environmental, Safety and Health Manager, BNI

The Environmental, Safety and Health (ES&H) Manager, BNI has the overall authority to interpret the regulations associated with this Procedure and provide guidance as to its intent and application.

2.3 Environmental, Safety and Health Representative, BNI

The ES&H Representative, BNI is responsible for:

- Overseeing compliance of this Procedure via review of field work activities
- Supplying technical advice and interpreting the ES&H codes in this Procedure

2.4 Responsible Superintendent

The Responsible Superintendent is responsible for:

- Being thoroughly familiar with this Procedure and having a full understanding of individual roles and responsibilities regarding compliance with and implementation of this Procedure
- Pre-planning work activities to identify the appropriate PPE to use
- Ensuring that workers understand the requirements of this Procedure

<i>Personal Protective Equipment and Safe Work Apparel</i>
--

2.5 Supervisor

The Supervisor is responsible for ensuring that the applicable safety controls and processes are incorporated into the planning and execution of the work, and that the workers are using the correct PPE for the assigned task.

2.6 PPE User/Worker

The PPE user/worker is responsible for:

- Using (wearing) PPE as required or specified by this Procedure, jobsite rules, and/or the job hazard analyses (JHAs)/permits
- Reporting situations where assigned PPE does not provide appropriate protection against the hazards that are present
- Inspecting PPE for defects, damage, and/or wear and tear that would make the PPE unsafe to use
- Wearing work apparel as required by this Procedure, company-specific dress standard requirements, and/or the JHAs/permits
- Maintaining work apparel or PPE in accordance with the requirements of this Procedure and the manufacturer's recommendations

3.0 REQUIREMENTS

The proper selection and use of PPE and safe apparel are important elements in the prevention of work-related injuries; however, PPE can only provide a level of protection against injuries and illnesses when it is maintained and used correctly.

This Procedure does not address every type of PPE that could be used at the UPF construction site. For each potentially hazardous task performed at the construction site, appropriate controls, including PPE, are identified and documented in the JHA. Only through appropriate planning can site hazards be determined and proper PPE identified and utilized.

The hazards present in any particular work activity or area and the risks they pose shall be evaluated, and adequate PPE shall be selected based on these evaluations. Key factors to be considered in the selection of PPE include the following:

- PPE shall be capable of providing protection against risk(s) without compromising individual safety
- PPE shall properly fit the user/worker
- PPE shall be compatible with the work to be performed
- PPE shall be of safe design and construction and in compliance with a nationally recognized standard for the work to be performed. Nationally recognized PPE standards include those from the following organizations:
 - American National Standards Institute (ANSI)
 - American Society for Testing and Materials (ASTM)
 - National Fire Protection Association (NFPA)

<i>Personal Protective Equipment and Safe Work Apparel</i>
--

- National Institute for Occupational Safety and Health (NIOSH)
- Underwriters Laboratories, Inc. (UL)
- PPE shall be used and maintained in a sanitary and reliable condition. PPE that has been altered beyond the manufacturer's recommendations is prohibited at the UPF construction site. Any such PPE shall be removed from the site and then either repaired or destroyed
- Specialized PPE, such as respirators or fall protection, requires additional training and/or medical qualifications before use. These items are outlined in their respective procedures

3.1 Criteria for PPE and Safe Work Apparel

The following subsections identify the various types of PPE utilized on the UPF Project.

3.1.1 Safe Work Apparel—Construction/Warehousing Areas

- Minimum safe work apparel requirements include:
 - Durable shirts with full-length sleeves (continuous) that cover the entire upper torso and arms. Shirts constructed of mesh and/or netting material are prohibited

NOTE: *Arm sleeves (synthetic/compression material) combined with short-sleeved shirts do not meet this requirement.*

- Full length durable pants in good condition that extend to the ankles
- Clothing made of natural fibers (e.g., cotton) is recommended
- Avoid wearing loose clothing, rings, and/or necklaces that may contact or get caught or tangled in moving parts, equipment, or energized systems

3.1.2 Footwear—Construction/Warehousing Areas

- Personnel assigned to or visiting Construction/Warehousing areas shall wear sturdy, ankle-high, safety-toed footwear that meet or exceed the requirements of ASTM F2413, *Standard Specification for Performance Requirements for Protective (Safety) Toe Cap Footwear*. Footwear such as tennis/athletic shoes, open-toed shoes, sandals, moccasins, high heels, boat shoes, and mules are not acceptable footwear
- Footwear must be in good condition, free from holes, tears, and other damage that impacts their protective qualities
- Use metatarsal guards in conjunction with the protective footwear as identified in the JHA for the task

3.1.2.1 Footwear—Construction/Warehousing Support Facilities

- Personnel assigned to or visiting Construction/Warehousing Support Facilities (e.g., office trailers or buildings) shall wear sturdy, closed-toed shoes in good condition with a maximum one-inch heel. Footwear such as open-toed shoes,

<i>Personal Protective Equipment and Safe Work Apparel</i>
--

sandals, moccasins, high heels, boat shoes, flats, mules, etc. are not acceptable footwear

3.1.3 Head Protection

- Hardhats must comply with ANSI Z89.1, *American National Standard for Industrial Head Protection*. Hardhats must be worn in accordance with the manufacturer's requirements and with the brim facing forward, unless the ES&H Manager or designee provides a written exception. Hardhats, other than those issued by the UPF, or current employer (subcontractor), are prohibited
- Do not wear a ball cap or any unapproved headgear under the hardhat. Hardhats fit best when worn directly on the head; however, some garments (e.g., bandanas, welding skullcaps, fabric winter liners, and tight-knit stocking caps) may be worn under the hardhat as long as these items do not diminish the protective properties of the hardhat
- Hardhats must be worn at all times while on the UPF construction site, with the following exceptions:
 - Inside an enclosed vehicle/equipment cab
 - In an office
 - Taking a break in a designated PPE-free area
 - Walking on a designated PPE-free pathway between the office/trailer building and the parking lot
- A hardhat must be worn in conjunction with a welding hood when performing welding or similar hot work operations
- The use of a welding hood alone without a hardhat is allowed if approved/authorized by the Responsible Superintendent and an ES&H Representative. This exemption may occur when welding needs to take place in a location that is physically restrictive and impedes the safe use of a hardhat. The use of alternative head/face protection must be evaluated and implemented as determined by the evaluation
- Store hardhats in a clean and dry location. Never use paint, solvents, hydrocarbon-type cleaners, glue, or other similar chemicals on hardhats. These substances can cause serious damage that may not be visible upon inspection
- Visually inspect the shell and suspension system of the hardhat daily for breakage, cracks, scratches, gouges, hairline cracks, discoloration, chalky appearance, or other unusual condition. Inspect the shell for brittleness by flexing the brim. Any of these conditions indicates a loss of protection from impact and electrical conductivity

3.1.3.1 Alternate Forms of Head Protection

- Alternate forms of head protection, such as bump caps or climbing helmets, may be suitable for select work tasks that require maneuvering in tight spaces with low overhead clearance or overhead hazards from falling/flying objects are not present.
- Use of an alternate form of head protection may be allowed when:

<i>Personal Protective Equipment and Safe Work Apparel</i>
--

- Hardhats have been demonstrated to be impractical or create an additional hazard
- There is no exposure to falling/flying objects that a hard hat would protect the user from
- The task is evaluated by the Responsible Superintendent and an ES&H Representative and documented on the Safety Task Analysis and Risk Reduction Talk (STARRT) card for the task

3.1.4 Eye and Face Protection

Eye protection (safety glasses) must meet the specifications of ANSI Z87.1, *American National Standard for Occupational and Educational Personal Eye and Face Protection Devices*.

- Do not wear non-photochromic glasses with tinted lenses inside a building or other structure with limited (temporary) illumination, regardless of whether they are prescription or non-prescription glasses
- Refer to ML-SH-801768-A002, *UPF Eye and Face Protection List*, for task-specific eye and face protection directives
- Wear eye protection at all times while on the UPF construction site or warehouse area, except when:
 - In an office or a trailer
 - Operating a vehicle or equipment inside an enclosed cab
 - Wearing goggles or respiratory protection that provides equal or greater levels of protection
- Personal prescription eyewear must have impact-rated (ANSI Z87.1) lens, frames, and permanently affixed side shields. If assistance is needed in determining whether specific glasses meet the ANSI standard, then contact a supervisor or an ES&H Representative
- Inspect eye and face protection for damage and wear and tear before each use. Before wearing safety glasses, inspect the frames for cracks and deformation and inspect the lenses for extensive scratches that limit visibility. Inspect goggles for pliability to ensure a good fit to the face. Check the headband and vents, if applicable, for signs of degradation and deterioration. Inspect face shields and suspension systems for breakage, cracks, scratches, and other detrimental conditions
- Safety glasses, goggles, and face shields may be cleaned with an eyeglass cleaner. Do not use ammonia, alkaline cleaners, abrasive cleaning compounds, or solvents

3.1.4.1 Goggles and Sealed Eyewear

Goggles and sealed eyewear (e.g., spoggles) may be required to provide protection from impact, dust, mists, and splashes that are generated by work activities.

Refer to ML-SH-801768-A002 and the activity JHA for task-specific eye and face protection directives.

<i>Personal Protective Equipment and Safe Work Apparel</i>
--

3.1.4.2 Face Shields

Face shields are required when workers are exposed to flying objects, molten metal, liquid chemicals, or potentially hazardous light radiation. Face shields shall be worn in conjunction with primary eye protection (safety glasses or goggles).

Refer to ML-SH-801768-A002 and the activity JHA for task-specific eye and face protection directives.

3.1.4.3 Welding Helmets (Hoods)

- Personnel performing welding activities shall wear a welding helmet (hood) that meets the requirements of ANSI Z87.1 to protect themselves from welding arc, sparks, and spatter
- Filter lenses shall be selected for the specific welding operation in accordance with ANSI Z49.1, *American National Standard for Safety in Welding, Cutting, and Allied Processes*, Table 1 – “Guide for Shade Numbers.” See **Appendix B, Guide for Shade Numbers in Welding**

NOTE: *Minimum shade requirements for welding operations are identified in the JHA for the activity.*

- Safety glasses or goggles must be worn in addition to the welding helmet
- Support personnel in the immediate welding area must wear a similar level of eye and face protection

3.1.5 Hearing Protection

Refer to UPF-CP-312, *Hearing Conservation Program*, for the selection and use of hearing protection equipment.

Care includes discarding disposable earplugs when they possess visible signs of uncleanness. Reusable earplugs and earmuffs must be cleaned and sanitized. Cleaned and sanitized reusable hearing protection must be kept in a clean, dry area.

Inspect reusable earplugs and earmuffs for wear and tear. Return damaged earmuffs for repair or disposal.

3.1.6 Hand Protection (Gloves)

- Hand protection shall be worn in all active Construction and Warehousing areas with the exception of designated PPE-free areas or for tasks that have been evaluated and require gloves to be removed (e.g., touchscreen use)
- Utilize hand protection appropriate for the hazards and the tasks to be performed. The following are for hand protection:
 - Impacts, cuts, abrasions, and infections
 - Extreme temperatures
 - Chemicals and other hazardous substances
 - Inspect hand protection before each use. Discard damaged and/or worn gloves with holes, tears, and/or other signs of deterioration

<i>Personal Protective Equipment and Safe Work Apparel</i>
--

3.1.6.1 Selection of Hand Protection

The following are for Hand Protection selection:

- Use only hand protection that is approved and provided by the Project. Refer to ML-SH-801768-A003, *UPF Gloves Matrix*, for a sample of Project approved hand protection.
- Selected hand protection must meet or exceed the following minimum requirements
 - Gloves must meet cut resistance equal to or greater than Level A5 as defined in ANSI/International Safety Equipment Association (ISEA) 105 (2016), *American National Standard for Hand Protection Classification*, or equivalent
 - Gloves must meet puncture resistance equal to or greater than Level 2 as defined in EN 388 2003, *Protective Gloves against Mechanical Risks*, or equivalent
 - Where impact hazards are identified (e.g., present risks to hands or fingers such as being caught in/between or struck by/against hazards), gloves with impact protection are required

NOTE 1: *Subcontractors shall provide gloves meeting these minimum requirements for standard use on the Project.*

NOTE 2: *Wearing gloves or loose clothing around rotating equipment can pose a risk of entanglement. An ES&H Representative and Responsible Superintendent will evaluate the task, equipment function, and manufacturer's instructions and provide recommendations for the task.*

3.1.7 Respiratory Protection Equipment

Refer to UPF-CP-318, *Respirator Use and Issuance*, for the selection, use, and care of respiratory protective equipment.

3.1.8 Fall Protection Equipment

Refer to UPF-MANUAL-SH-A001, *UPF Elevated Work Manual*, for the selection, use, and care of fall protection equipment.

3.1.9 Electrical Protection Equipment

Refer to UPF-MANUAL-CM-001, *Uranium Processing Facility Construction Electrical Safety Manual*, for the selection, use, and care of electrical protective equipment.

3.1.10 High-Visibility Apparel

Wear appropriate, high-visibility apparel when required in accordance with **Table 1**. High-visibility apparel includes safety vests, jackets, shirts, and other personal protective safety clothing that is intended to provide visibility during both daytime and nighttime usage and that meets the Performance Class 2 requirements of ANSI 107, *American National Standard for High-Visibility Apparel and Headwear*.

Personal Protective Equipment and Safe Work Apparel

Table 1. Appropriate Apparel

PERSONNEL	APPAREL COLOR
Safety Watches: <ul style="list-style-type: none"> • Traffic Watch (Flagger) • Fire Watch • Confined Space Attendant 	Orange
Personnel Directing Crane Equipment: <ul style="list-style-type: none"> • Signalman (crane), Bellman 	Red
Excavation and Backfill Personnel (Personnel working within an excavation area where heavy equipment is operating)	Yellow/Lime Green
Personnel as directed by the Site Manager and ES&H Manager (e.g., K-31, Laydown 2, Alpha/Bravo/Charlie Area)	Yellow/Lime Green

3.1.11 Body Protection

Specific body protection/clothing may be required for specialized work tasks. The JHA will identify the specific body protection/clothing required.

3.1.11.1 Welding and Associated Hot Work Activities

Clothing shall be selected to minimize the potential for ignition, burning, entrapment of hot sparks, or electric shock. Personnel performing welding and associated hot work activities shall:

- Wear a shirt, jacket, or equivalent that meets the requirements of hazard risk category 2 (in accordance with NFPA 2112, *Standard on Flame-Resistant Clothing for Protection of Industrial Personnel Against Short-Duration Thermal Exposures from Fire*)
- Wear pants/trousers made from heavier materials (e.g., heavy cotton, denim) that overlap footwear to prevent spatter from entering
- Keep sleeves and collars buttoned
- Wear clothing that is free from pockets, hoods, or cuffs that can trap sparks or slag

NOTE: *Pockets that are covered or equipped with closeable flaps are acceptable.*

Body protection requirements for awkward or confined hot work positions (e.g., prone, crouching) include hazard risk category 2 pants, trousers, or leggings.

Leather cape sleeves or shoulder covers made of leather or flame-resistant material may be required while performing hot work in an overhead configuration.

Additional evaluation of hot work PPE will be performed during the hot work permit process and pre-job/STARRT card briefing.

4.0 RECORDS

None

5.0 REFERENCES

5.1 Source References

10 Code of Federal Regulations (CFR) 851, *Worker Safety and Health Program*

29 CFR 1926, *Occupational Safety and Health Regulations for Construction*,
Subpart E, *Personal Protective and Life Saving Equipment*

Bechtel Corporation, ES&H Core Process 2HI-H030-00205, *Personal Protective Equipment*

Bechtel Corporation, ES&H Procedure 2HO-E0S0-00001, *Hand Protection*

NFPA 70E, *Standard for Electrical Safety in the Workplace*

UPF-CP-200, *UPF General Safe Work Practices*

UPF-CP-227, *UPF Safety Watches*

Y73-95-802, *Confined Space Entry Program*

5.2 Interfacing References

ANSI Z49.1, *American National Standard for Safety in Welding, Cutting, and Allied Processes*

ANSI Z87.1, *American National Standard for Occupational and Educational Personal Eye and Face Protection Devices*

ANSI Z89.1, *American National Standard for Industrial Head Protection*

ANSI 107, *American National Standard for High-Visibility Apparel and Headwear*

ANSI/ISEA 105 (2016), *American National Standard for Hand Protection Classification*

ASTM F2413, *Standard Specification for Performance Requirements for Protective (Safety) Toe Cap Footwear*

EN 388 2003, *Guide to Safety Glove Standard Gloves Giving Protection to Mechanical Risks*

E-POL-0050, *Standards of Conduct and Appearance*

ML-SH-801768-A002, *UPF Eye and Face Protection List*

ML-SH-801768-A003, *UPF Gloves Matrix*

NFPA 2112, *Standard on Flame-Resistant Clothing for Protection of Industrial Personnel Against Short-Duration Thermal Exposures from Fire*

UPF-CP-312, *Hearing Conservation Program*

UPF-CP-318, *Respirator Use and Issuance*

UPF-MANUAL-CM-001, *Uranium Processing Facility Construction Electrical Safety Manual*

UPF-MANUAL-SH-A001, *UPF Elevated Work Manual*

6.0 SUPPLEMENTAL INFORMATION

Appendix A, *Acronyms and Definitions*

Appendix B, *Guide for Shade Numbers in Welding*

APPENDIX A

Acronyms and Definitions

Acronyms

ANSI	American National Standards Institute
ASTM	American Society for Testing and Materials
CFR	Code of Federal Regulations
ES&H	Environmental, Safety and Health
ISEA	International Safety Equipment Association
JHA	Job Hazard Analysis
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
PPE	Personal Protective Equipment
PRMS	Programmatic Requirements Management System
STARRT	Safety Task Analysis and Risk Reduction Talk
UL	Underwriters Laboratories, Inc.
UPF	Uranium Processing Facility

Definitions

Apparel	Clothing worn to cover the body and extremities, including shirts, pants, jackets, raincoats, etc.
Construction/ Warehousing Support Facilities	Offices and break areas directly supporting construction or warehousing activities, but where physical work is not being performed (e.g., Construction Support Building, On-boarding Center, craft break trailers, warehouse support trailers).
Job Hazard Analysis	A tool used to document workplace activities and related hazards and controls.
Personal Protective Equipment	Safety devices or garments used to protect workers from injury or exposure resulting from contact with chemical, biological, physical, or workplace hazards.
Photochromic Glasses	Eyeglass lenses that darken automatically when exposed to sunlight and then fade back when returning indoors.

Personal Protective Equipment and Safe Work Apparel

APPENDIX B

Guide for Shade Numbers in Welding

ANSI Z49.1:2012

Table 1
Guide for Shade Numbers
 (from AWS F2.2:2001(R2010), *Lens Shade Selector*)
 Shade numbers are given as a guide only and may be varied to suit individual needs.

Process	Electrode Size in (mm)	Arc Current (Amperes)	Minimum	Suggested ^a
			Protective Shade	Shade No. (Comfort)
Shielded Metal Arc Welding (SMAW)	Less than 3/32 (2.4)	Less than 60	7	—
	3/32–5/32 (2.4–4.0)	60–160	8	10
	5/32–1/4 (4.0–6.4)	160–250	10	12
	More than 1/4 (6.4)	250–550	11	14
Gas Metal Arc Welding (GMAW) and Flux Cored Arc Welding (FCAW)		Less than 60	7	—
		60–160	10	11
		160–250	10	12
		250–500	10	14
Gas Tungsten Arc Welding (GTAW)		Less than 50	8	10
		50–150	8	12
		150–500	10	14
Air Carbon Arc (Light) Cutting (CAC-A) (Heavy)		Less than 500	10	12
		500–1000	11	14
Plasma Arc Welding (PAW)		Less than 20	6	6 to 8
		20–100	8	10
		100–400	10	12
		400–800	11	14
Plasma Arc Cutting (PAC)		Less than 20	4	4
		20–40	5	5
		40–60	6	6
		60–80	8	8
		80–300	8	9
		300–400	9	12
	400–800	10	14	
Torch Brazing (TB)		—	—	3 or 4
Torch Soldering (TS)		—	—	2
Carbon Arc Welding (CAW)		—	—	14
	Plate Thickness			Suggested ^a
	in	mm		Shade No. (Comfort)
Oxyfuel Gas Welding (OFW)				
	Light	Under 1/8	Under 3	4 or 5
	Medium	1/8 to 1/2	3 to 13	5 or 6
Heavy	Over 1/2	Over 13	6 or 8	6 or 8
Oxygen Cutting (OC)				
	Light	Under 1	Under 25	3 or 4
	Medium	1 to 6	25 to 150	4 or 5
Heavy	Over 6	Over 150	5 or 6	5 or 6

^a As a rule of thumb, start with a shade that is too dark to see the weld zone. Then go to a lighter shade which gives sufficient view of the weld zone without going below the minimum. In oxyfuel gas welding, cutting, or brazing where the torch and/or the flux produces a high yellow light, it is desirable to use a filter lens that absorbs the yellow or sodium line of the visible light spectrum.